

Outdoor Cameras

JCC-MIR463WHQ

1/3" High Res. Color IR HQ1 Camera with Auto Iris Lens



Features

- 1/3" Sony Super HAD Color CCD Sensor
- Sony HQ1 Digital Signal Processor
- NTSC:811x508/PAL:795x598 Pixels
- 540 TV Lines /0 Lux with IR
- Automatic Gain Control
- Auto Electronic Shutter
- Auto White Balance
- BLC & Flickerless (F.L.) On/Off Adjustable
- Mechanical IR-cut Filter built in
- 15 x 850nm IR-LED Built-in
- IP 67 Waterproof Standard
- IR Illuminating Distance:
Indoor:30~40M Outdoor:20~30M
- 3.8~9.5mm D/N Aspherical Auto Iris Lens
Built-in
- DC 12V

Specification

Model	JCC-MIR463WHQ
Pick Up Element	1/3" Sony Super HAD Color CCD Sensor
D.S.P.	Sony HQ1 Digital Signal Processor
Picture Element	NTSC: 811(H) x 508(V) ; PAL: 795(H) x 598(V)
Horizontal Frequency	NTSC: 15.734 KHz ; PAL: 15.625 KHz
Vertical Frequency	NTSC: 59.94 Hz ; PAL: 50 Hz
Synchronization	Internal/ Negative Sync.
Scanning System	2 : 1 Interlace
Resolution	Horizontal 540 TV Lines
Low-light Sensitivity	0 Lux with IR (IR-LED ON under 4 Lux)
S/N Ratio	More than 48 dB (AGC OFF)
Electronic Shutter	Auto: 1/60 (50) sec. ~ 1/100,000 sec.
Gamma Correction	0.45
Gain Control	Auto Gain Control (AGC)
Flickerless (F.L.)	Flickerless On / Off Adjustable
Backlight Compensation	BLC On / Off Adjustable
White Balance	ATW
Lens Built-in	3.8mm~9.5mm/F1.3 D/N Aspherical Auto Iris Lens / 74.2~30 degree
Video Output	1.0 Vp-p Composite Video Output ; 75 Ohm
Power Source	DC 12V
Waterproof Standard	IP 67 Waterproof Standard
Operating Temperature	- 10° ~ +50 °C / RH 85% or Less
Power Consumption	Max. 3.5 W
Dimension	81.4mm (Dia.) x140mm (L)
Weight	490 Grams
IR Illuminator Module	
Infra Red Luminary	15 x 850nm IR-LED, Life: 6,000 Hours ; Controlled by CDS Sensor
Wavelength	850 nm
Beam Spread Angle	30 Ddegree of Beam Spread Angle with 90 Degree of Projection Angle
Illuminating Distance	15 ~ 20 Meters
Illuminator Active Limit	Under 10 Lux (with Linear Control)

Dimensions

