

High Res. Vandal-Resistant Color HQ IR Dome

JCC-VA848HQVD

1/3" High-Res. Vandal-Resistant Color Varifocal HQ1 IR Dome



Features

- 1/3" Sony Super HAD CCD Sensor
- Sony 10-bit HQ1 Digital Signal Processor
- NTSC:811x508 / PAL:795x596 Pixels
- 540 TVL/0.25 Lux@F1.2
- AGC On/Off Adjustable
- AES On/Off Adjustable
- Flickerless On/Off Adjustable
- BLC On/Off Adjustable
- Auto White Balance
- 3-Axis Mechanism
- 2.9-10.0mm/F1.2 Aspherical Auto Iris Lens
- Vandal proof and Ip66 Water proof level
- DC 12V
- Unique 3 Axis Mechanism
- Optional Lens:
9.0-22.0mm / F1.5 Auto Iris Lens




3-Axis Mechanism




Specification

Model	JCC-VA848HQVD
Pick Up Element	1/3" Sony Super HAD Color CCD Sensor
D.S.P	Sony 10-bit HQ1 Digital Signal Processor
Picture Element	NTSC: 811 (H) x 508(V); PAL: 795(H) x 596(V)
Horizontal Frequency	NTSC: 15.734 KHz.; PAL: 15.625 KHz.
Vertical Frequency	NTSC: 59.94 Hz.; PAL: 50 Hz.
Synchronization	Internal
Scanning System	2 : 1 Interlace
Resolution	Horizontal 540 TV Lines
Sensitivity	0.25Lux@F1.2
S/N Ratio	More than 48 dB (AGC Off)
White Balance	Auto
Backlight Compensation	BLC On/Off Adjustable
Gain Control	AGC On/Off Adjustable
Flickerless (F.L.)	On/Off Adjustable
Electronic Shutter	Auto : 1/60 (50) sec. ~ 1/100,000 sec.
Gamma Correction	0.45
Lens Built-in	Standard:f2.9mm~10mm/F1.2 Aspherical Auto Iris Lens / 94.6°~28.8°
Video Output	1.0 Vp-p Composite Video Output; 75 Ohms
Operating Temperature	- 10 °C ~ +50 °C / RH 85% or Less
Power Consumption	Max. 2.3W
Power Supply	DC12V
Dimension	112.2mm (Dia.) x 140mm(H)
Weight	950 Grams
Optional Lens	9.0mm ~ 22.0mm / F1.5 Auto Iris lens
Water Resistance	IP66

Dimension



Optional



Ceiling-mount Bracket (Optional)

■ ECB-04



■ WMB-04