

Weatherproof Vari-focal Cameras

JCC-MIR482W

1/3" Color IR Camera with IR Cut Filter



JCC-MIR482WHQ

1/3" High Res. HQ1 Color IR Camera with IR Cut Filter



ZOOMING
FOCUSING



Features

- IR projecting distance 40 meters in dark view
- Water resistant with aluminum die-cast pass IP 66 test
- Easy to install either indoor or outdoor application
- Integrated auto iris vari-focal IR lens wide zooming range with adjustable focal length in 2.9~10 mm
- Anti-thunder circuit prevents tube struck by thunder
- Option: true day & night solution (with mechanical switching IR-Cut filter)

Specification

Model	JCC-MIR482W	JCC-MIR482WHQ
Image Pick-up Device	1/3" color CCD sensor interline	
Effective Picture Elements	NTSC: 510 (H) × 492 (V) PAL: 500 (H) × 582 (V)	NTSC: 768 (H) × 494 (V) PAL: 752 (H) × 582 (V)
Synchronizing System	Internal	
Horizontal Resolution	380 Horizontal TV Lines	540 Horizontal TV Lines
Electronic Shutter control	off	
Minimum illumination	1.0 Lux / F1.8 IR on 0 Lux	0.5 Lux / F1.8 IR on 0 Lux
Low-light Sensitivity	0 Lux with IR	
Auto Electronic Shutter	NTSC: 1/60~1/100,000 Sec.; PAL: 1/50~1/100,000 Sec.	
Gamma Characteristic	0.45	
S/N Ratio	More than 48dB (AGC Off)	
Emitting wavelength of LED	850nm	
Emitting angle of LED	40	
Video Output	1 Vp-p 75 ohm, BNC Connector	
White Balance	Automatically (2500°K~9500°K)	
Backlight Compensation	Yes	
Gain Control	Yes	
Lens Furnished	2.9 – 10 mm with Auto Iris	
Waterproof Standard	IP 66 Waterproof Standard	
Power requirements	AC 90~260 V	
Operating Temp.	-10°C ~ 50°C	
Storage Temperature	-30°C ~ 80°C	
IR Project Distance	40M	
Dimensions	305 (L) x 110 (W) x 115 (H) mm	
Weight	2.0 Kgs	