

# Bullet Cameras

## JBC-323

1/3" B/W Bullet Camera



## JCC-423

1/4" Color Bullet Camera



## Features

- JBC-323: EIA: 537x 505  
CCIR: 537 x 597 Pixels
- JCC-423: NTSC: 537x 505 Pixels  
PAL: 537 x 597 Pixels
- 420 TV Lines (JBC-323)  
330 TV Lines (JCC-423)
- 0.3 Lux @F2.0 (JBC-323)  
0.5 Lux @F2.0 (JCC-423)
- IP 66 Waterproof Standard
- Auto Gain Control
- Auto Electronic Shutter
- 3.6mm/F2.0 Board Lens
- Miniature Bracket Included
- DC 12V

## Specification

Model	JBC-323	JCC-423
Image Sensor	1/3" B/W CCD Sensor	1/4" Sony Super HAD CCD Sensor
Picture Element	EIA: 537(H) x 505(V) CCIR: 537(H) x 597(V)	NTSC: 537(H) x 505(V) PAL: 537(H) x 597(V)
Horizontal Frequency	EIA: 15.734 KHz. ; CCIR: 15.625 KHz.	NTSC: 15.734 KHz. ; PAL: 15.625 KHz.
Vertical Frequency	EIA: 59.94 Hz. ; CCIR: 50 Hz.	NTSC: 59.94 Hz. ; PAL: 50 Hz.
Scanning System	2 : 1 Interlace	
Synchronization	Internal	
Resolution	Horizontal 420 TV Lines	Horizontal 330 TV Lines
Low-light Sensitivity	0.3 Lux @F2.0	0.5 Lux @F2.0
S/N Ratio	More than 48 dB (AGC OFF)	
Electronic Shutter	Auto: 1/60 (50) sec. ~ 1/100,000 sec	
White Balance	N/A	Auto White Balance (2500 K ~ 9500 K)
Gain Control	Auto Gain Control (AGC)	
Waterproof Standard	IP 66 Waterproof Standard	
Lens Built-in	3.6mm/F2.0 Board Lens	
Video Output	1.0 Vp-p Composite Video Output ; 75 Ohm	
Power Supply	DC 12V	
Power Consumption	Max. 1.44 W	
Operating Temperature	- 10 ~ 50 ° C ( 14 ~ 122 ° F)	
Dimension	28mm (Dia.) x 89.6mm (L)	
Weight	200 Grams	
Audio(Optional)	2V p-p 500hms.RCA connector	

## Dimension

